

Teton

6 Colors





Teton

LVT02

Style: LVT02

Flooring Type: 3mm Glue Down w/Beveled Edge

Wear Layer: 22mil Total Wear Surface

Commercial Warranty: 15 Year Limited

Size: 6.3" x 48"

Installation Method: Glue Down



Saddle HF301



Castle Grey HF315



Indian Summer HF307



Cappuccino HF319



Grey Fox HF311



Sawtooth Grey HF332

Tongass
8 Colors





Tongass

LVT01

Style: LVT01

Flooring Type: 3mm + 1.5mm Cork Back
w/Beveled Edge

Wear Layer: 30mil Total Wear Surface

Commercial Warranty: 15 Year Limited

Size: 6.3" x 48"

Installation Method: Glue Down



Grey Fox HF351



Driftwood HF355



Sawtooth Grey HF352



Weathered Teak HF356



Red Oak HF353



Cappuccino HF357



Castle Gray HF354



Indian Summer HF358

Timber
5 Colors



Timber

LVT03

Style: LVT03

Flooring Type: 5mm Loose Lay w/Beveled Edge

Wear Layer: 22mil Total Wear Surface

Commercial Warranty: 20 Year Limited

Size: 9" x 48"

Installation Method: Loose Lay



Midnight HF750



Sawtooth Grey HF753



Caramel HF751



Ashwood HF754



Foxwood HF752



Features + Benefits

- UV Cured Polyurethane Finish
- 100% Waterproof
- Anti-Microbial
- Anti-Scratch
- Anti-Slip
- FloorScore® Certified
- Serviced from US Inventory

Feature	Advantage	Benefit
UV Cured Polyurethane Finish	No wax finish	Maintenance savings in time and money
100% Waterproof	Dimensional stability	Does not react to sitting or flooding in terms of shrinkage or deterioration
Anti-Microbial	Does not support or sustain any micro organism growth.	Inherently resistant to growth of bio organisms
Anti-Scratch	PPG Polyurethane protects wear layer and film	Reduces signs of wear and tear through resisting and masking scratching.
Anti-Slip/In Line Embossing	Embossed products provide definition of design and create a coefficient of friction	Less slippery than an non-embossed product while providing more realistic looks.
FloorScore® Certified	Third party certification of environmental attributes and content	Assurance of product ingredients and
Cork Backing (Tongass Only)	Improved comfort underfoot and noise reduction (IIC of 58)	Greater guest satisfaction
Serviced from US Inventory	Quick ship	Shorter lead times



Dedicated Primer & Adhesive

+

- HS225 Universal Primer (1 gal)
- HFS Transitional Pressure Sensitive (TPS™) Adhesive (4 gal)